

KATALOG PRODUK



SPEKIFIKASI PRODUK

DESCRIPTION	TIPE	
	L	SK
INPUT	50 V - 130 V 140 V - 240 V	50 V - 130 V 100 V - 240 V
OUTPUT, RATE CURRENT	110 V / 220 V, 6,5 A	110 V / 220 V, 6,5 A
DIMENSION	P=19 x L=21 x T=16 Cm ³	P=16 x L=19 x T=14 Cm ³
BERAT	5,5 Kg	6,5 Kg
FREQUENCY	50 Hz	
OUTPUT DEVIANCE	± 2%	
READING METER	Analog Volt Meter Output	
PROTECTION OUTPUT	Fuse Kaca	
RESPON TIME	≤1,5s (Against 10% Input Voltage Deviation)	
EFFICIENCY	Better than 90% (Input 180 V, Output 220 V)	
AMBIENT TEMPERATURE	-5°C until +40°C	
AMBIENT HUMIDITY	Less than 90% (Relative Humidity)	
TEMPERATURE RISE	Less than 70% (Input 180 V, Output 220 V)	
WORKING SYSTEM	Automatic	
CONTROL SYSTEM	DC Servo Motor	
COOLING SYSTEM	Air Natural	
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform	
INSTALLATION	Indoor	

