

# KATALOG PRODUK



-  **OVER VOLTAGE PROTECTION**
-  **LOW VOLTAGE PROTECTION**
-  **OVER TEMP PROTECTION**
-  **DELAY TIME**

# SPEKIFIKASI PRODUK

DESCRIPTION	TIPE		
	LD	KD	SKD
INPUT	260 V - 415 V	240 V - 415 V	175 V - 415 V
OUTPUT	380 V / 220 V	380 V / 220 V	380 V / 220 V
RATED CURRENT	34 A	34 A	34 A
DIMENSION	P=58 x L=50 x L=102 Cm <sup>3</sup>	P=58 x L=50 x L=102 Cm <sup>3</sup>	P=66 x L=54 x T=102 Cm <sup>3</sup>
BERAT	130 Kg	139 Kg	160 Kg

FREQUENCY	50 Hz
OUTPUT DEVIANCE	± 2% - 5% Adjustable
READING METER	Digital / LCD Input & Output Volt Meter & Input Ampere Meter
PROTECTION OUTPUT	Over Voltage ± 238 V Automatic Cut Off
RESPONSE TIME	≤ 1s ( Against 10% Input Voltage Deviation )
EFFICIENCY	Better than 98% ( Input 180 V, Output 220 V / Phase )
AMBIENT TEMPRATURE	- 5 °C until + 40 °C
AMBIENT HUMIDITY	Less than 90% ( Relative Humidity )
TEMPRATURE RISE	Less than 70% ( Input Volt 180 V, Output Volt 220 V / Phase )
WORKING SYSTEM	Automatic
CONTROL SYSTEM	DC Servo Motor (Tsukasa Jepang )
COOLING SYSTEM	Cooling Fan
DI-ELECTRIC STRENGTH	1500 V/min
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform
INSTALLATION	Indoor

