


KATALOG PRODUK



SPEKIFIKASI PRODUK

DESCRIPTION	TYPE		
	LD	KD	SKD
INPUT	50 V - 130 V 140 V - 240 V	50 V - 130 V 130 V - 240 V	50 V - 130 V 100 V - 240 V
OUTPUT, RATED CURRENT	110 V - 220 V, 13,5 A	110 V / 220 V, 13,5 A	110 V / 220 V, 13,5 A
DIMENSION	P=30 x L=23 x T=23 Cm ³	P=30 x L=23 x T=23 Cm ³	P=31 x L=25 x T=23 Cm ³
BERAT	13 Kg	13 Kg	14 Kg

FREQUENCY	50 Hz
OUTPUT DEVIANCE	± 2% - 5% Adjustable
READING METER	Digital / LCD Volt Meter & Ampere Meter
PROTECTION OUTPUT	Over Voltage ± 238 V Automatic Cut Off
RESPONSE TIME	≤ 1s (Against 10% Input Voltage Deviation)
EFFICIENCY	Better than 98% (Input 180 V, Output 220 V)
AMBIENT TEMPERATURE	- 5 °C until + 40 °C
AMBIENT HUMIDITY	Less than 90% (Relative Humidity)
TEMPRATURE RISE	Less than 70% (Input Volt 180 V, Output Volt 220 V)
WORKING SYSTEM	Automatic
CONTROL SYSTEM	DC Servo Motor
COOLING SYSTEM	Cooling Fan
DI-ELECTRIC STRENGTH	1500 V/Min
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform
INSTALLATION	Indoor

