



KATALOG PRODUK



OVER VOLTAGE PROTECTION



LOW VOLTAGE PROTECTION



OVER TEMP PROTECTION



DELAY TIME

SPEKIFIKASI PRODUK

DESCRIPTION	TIBE		
	LD	KD	SKD
INPUT	260 V - 415 V	240 V - 415 V	175 V - 415 V
OUTPUT	380 V / 220 V	380 V / 220 V	380 V / 220 V
RATED CURRENT	45 A	45 A	45 A
DIMENSION	P=58 x L=50 x T=102 Cm ³	P=58 x L=50 x T=102 Cm ³	P=66 x L=54 x T=122 Cm ³
BERAT	141 Kg	153 Kg	204 Kg

FREQUENCY	50 Hz
OUTPUT DEVIANCE	± 2% - 5% Adjustable
READING METER	Digital / LCD Input & output Volt Meter, & Input Ampere Meter
PROTECTION OUTPUT	Over Voltage ± 238 V / Phase, Automatic Cut Off
RESPONSE TIME	≤ 1s (Against 10% Input Voltage Deviation)
EFFICIENCY	Better than 98% (Input 180 V, Output 220 V / Phase)
AMBIENT TEMPERATURE	- 5 °C until + 40°C
AMBIENT HUMIDITY	Less than 90% (Relative Humidity)
TEMPERATURE RISE	Less than 70% (Input Volt 180 V, Output Volt 220 V / Phase)
WORKING SYSTEM	Automatic
CONTROL SYSTEM	DC Servo Motor (Tsukasa Jepang)
COOLING SYSTEM	Cooling Fan
DI-ELECTRIC STRENGTH	1500 V/Min
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform
INSTALLATION	Indoor

