

KATALOG PRODUK



SPEKIFIKASI PRODUK

DESCRIPTION	TIPE		
	LD	KD	SKD
INPUT	260 V - 415 V	240 V - 415 V	175 V - 415 V
OUTPUT	380 V / 220 V	380 V / 220 V	380 V / 220 V
RATED CURRENT	13 A	13 A	13 A
DIMENSION	P=38 x L=31 x L=83 Cm ³	P=38 x L=31 x L=83 Cm ³	P=42 x L=32 x T=83 Cm ³
BERAT	43 Kg	43 Kg	60 Kg

FREQUENCY	50 Hz
OUTPUT DEVIANCE	± 2% - 5% Adjustable
READING METER	Digital / LCD Input & Output Volt Meter & Input Ampere Meter
PROTECTION OUTPUT	Over Voltage ± 238 V Automatic Cut Off
RESPONSE TIME	≤ 1s (Against 10% Input Voltage Deviation)
EFFICIENCY	Better than 98% (Input 180 V, Output 220 V / Phase)
AMBIENT TEMPRATURE	- 5 °C until + 40 °C
AMBIENT HUMIDITY	Less than 90% (Relative Humidity)
TEMPRATURE RISE	Less than 70% (Input Volt 180 V, Output Volt 220 V / Phase)
WORKING SYSTEM	Automatic
CONTROL SYSTEM	DC Servo Motor
COOLING SYSTEM	Cooling Fan
DI-ELECTRIC STRENGTH	1500 V/min
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform
INSTALLATION	Indoor

