


**OVER VOLTAGE  
PROTECTION**

**LOW VOLTAGE  
PROTECTION**


**OVER TEMP  
PROTECTION**

**DELAY TIME**

# SPEKIFIKASI PRODUK

DESCRIPTION	TIPE		
	LD	KD	SKD
INPUT	160 V - 240 V	130 V - 240 V	100 V - 240 V
OUTPUT	220 V	220 V	220 V
RATED CURRENT	90 A	90 A	90 A
DIMENSION	P=56 x L=65 x T=130Cm <sup>3</sup>	P=56 x L=65 x T=130Cm <sup>3</sup>	P=61 x L=75 x T=135Cm <sup>3</sup>
BERAT	172 Kg	177 Kg	258 Kg

FREQUENCY	50 Hz
OUTPUT DEVIANCE	± 2% - 5% Adjustable
READING METER	Digital Input & Output Volt Meter, & Input Ampere Meter
PROTECTION OUTPUT	Over Voltage ± 238 V Automatic Cut Off
RESPONSE TIME	≤ 1s ( Against 10% Input Voltage Deviation )
EFFICIENCY	Better than 98% ( Input 180 V, Output 220 V )
AMBIENT TEMPERATURE	- 5 °C until + 40°C
AMBIENT HUMIDITY	Less than 90% ( Relative Humidity )
TEMPERATURE RISE	Less than 70% ( Input Volt 180V , Output Volt 220 V )
WORKING SYSTEM	Automatic
CONTROL SYSTEM	AC Servo Motor
COOLING SYSTEM	Cooling Fan
DI-ELECTRIC STRENGTH	1500 V/Min
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform
INSTALLATION	Indoor


**Dual Controller Board**
