

KATALOG PRODUK


OVER VOLTAGE PROTECTION

LOW VOLTAGE PROTECTION


OVER TEMP PROTECTION

DELAY TIME

SPEKIFIKASI PRODUK

| DESCRIPTION | TIPE | | |
|---------------|-------------------------------------|-------------------------------------|-------------------------------------|
| | LD | KD | SKD |
| INPUT | 160 V - 240 V | 130 V - 240 V | 100 V - 240 V |
| OUTPUT | 220 V | 220 V | 220 V |
| RATED CURRENT | 90 A | 90 A | 90 A |
| DIMENSION | P=56 x L=65 x L=130 Cm ³ | P=56 x L=65 x L=130 Cm ³ | P=61 x L=75 x T=135 Cm ³ |
| BERAT | 215 Kg | 220 Kg | 327 Kg |

| | |
|----------------------|--|
| FREQUENCY | 50 Hz |
| OUTPUT DEVIANCE | ± 2% - 5% Adjustable |
| READING METER | Digital Input & Output Volt Meter & Input Ampere Meter |
| PROTECTION OUTPUT | Over Voltage ± 238 V Automatic Cut Off |
| RESPONSE TIME | ≤ 1s (Against 10% Input Voltage Deviation) |
| EFFICIENCY | Better than 98% (Input 180 V, Output 220 V) |
| AMBIENT TEMPRATURE | - 5 °C until + 40 °C |
| AMBIENT HUMIDITY | Less than 90% (Relative Humidity) |
| TEMPRATURE RISE | Less than 70% (Input Volt 180 V, Output Volt 220 V) |
| WORKING SYSTEM | Automatic |
| CONTROL SYSTEM | AC Servo Motor |
| COOLING SYSTEM | Cooling Fan |
| DI-ELECTRIC STRENGTH | 1500 V/Min |
| WAVEFORM DISTORTION | Non-Lack Fidelity Waveform |
| INSTALLATION | Indoor |


Dual Controller Board
