



# KATALOG PRODUK

**MODEL**  
**SBW 100 KVA**

3 Phase (380V)



OVER VOLTAGE  
PROTECTION



LOW VOLTAGE  
PROTECTION



OVER TEMP  
PROTECTION



DELAY TIME

# SPEKIFIKASI PRODUK

DESCRIPTION	TIPE		
	LD	KD	SKD
INPUT	280 V - 430 V	240 V - 415 V	175 V - 415 V
OUTPUT	380 V / 220 V	380 V / 220 V	380 V / 220 V
RATED CURRENT	150 A	150 A	150 A
DIMENSION	P=90 x L=115 x T=162 Cm <sup>3</sup>	P=90 x L=115 x T=162 Cm <sup>3</sup>	P=90 x L=115 x T=162 Cm <sup>3</sup>
BERAT	614 Kg	714 Kg	820 Kg

FREQUENCY	50 Hz
OUTPUT DEVIANCE	± 2% - 5% Adjustable
READING METER	Digital Input & output Volt Meter, & Input Ampere Meter
PROTECTION OUTPUT	Over Voltage ± 238 V / Phase, Automatic Cut Off
RESPONSE TIME	≤ 1s ( Against 10% Input Voltage Deviation )
EFFICIENCY	Better than 98% ( Input 180 V, Output 220 V / Phase )
AMBIENT TEMPRATURE	- 5 °C until + 40°C
AMBIENT HUMIDITY	Less than 90% ( Relative Humidity )
TEMPRATURE RISE	Less than 70% ( Input Volt 180 V, Output Volt 220 V / Phase )
WORKING SYSTEM	Automatic
CONTROL SYSTEM	AC Servo Motor
COOLING SYSTEM	Cooling Fan
DI-ELECTRIC STRENGTH	1500 V/Min
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform
INSTALLATION	Indoor

