

KATALOG PRODUK


OVER VOLTAGE PROTECTION

LOW VOLTAGE PROTECTION

OVER TEMP PROTECTION

DELAY TIME

SPEKIFIKASI PRODUK

| DESCRIPTION | TIPE | | |
|---------------|--------------------------------------|--------------------------------------|--------------------------------------|
| | LD | KD | SKD |
| INPUT | 280 V - 430 V | 240 V - 415 V | 175 V - 415 V |
| OUTPUT | 380 V / 220 V | 380 V / 220 V | 380 V / 220 V |
| RATED CURRENT | 180 A | 180 A | 180 A |
| DIMENSION | P=90 x L=115 x T=177 Cm ³ | P=90 x L=115 x T=177 Cm ³ | P=90 x L=115 x T=177 Cm ³ |
| BERAT | 655 Kg | 815 Kg | 964 Kg |

| | |
|----------------------|---|
| FREQUENCY | 50 Hz |
| OUTPUT DEVIANCE | ± 2% - 5% Adjustable |
| READING METER | Digital Input & Output Volt Meter & Input Ampere Meter |
| PROTECTION OUTPUT | Over Voltage ± 238 V / Phase, Automatic Cut Off |
| RESPONSE TIME | ≤ 1s (Against 10% Input Voltage Deviation) |
| EFFICIENCY | Better than 98% (Input 180 V, Output 220 V / Phase) |
| AMBIENT TEMPRATURE | - 5 °C until + 40°C |
| AMBIENT HUMIDITY | Less than 90% (Relative Humidity) |
| TEMPRATURE RISE | Less than 70% (Input Volt 180 V, Output Volt 220 V / Phase) |
| WORKING SYSTEM | Automatic |
| CONTROL SYSTEM | AC Servo Motor |
| COOLING SYSTEM | Cooling Fan |
| DI-ELECTRIC STRENGTH | 1500 V/Min |
| WAVEFORM DISTORTION | Non-Lack Fidelity Waveform |
| INSTALLATION | Indoor |

