



KATALOG PRODUK



SPEKIFIKASI PRODUK

DESCRIPTION	TIPE LD	
INPUT	280 V - 430 V	
OUTPUT	380 V / 220 V	
RATED CURRENT	2.250 A	
FREQUENCY	50 Hz	
OUTPUT DEVIANCE	± 1% - 5% Adjustable / Customizable Program	
READING METER	Digital Input & Output Volt Meter & Input Ampere Meter	
PROTECTION OUTPUT	Over Voltage ± 238 V / Phase, Automatic Cut Off	
RESPONSE TIME	≤ 1s (Against 10% Input Voltage Deviation)	
EFFICIENCY	Better than 98% (Input 180 V, Output 220 V / Phase)	
AMBIENT TEMPRATURE	- 5 °C until + 40°C	
AMBIENT HUMIDITY	Less than 90% (Relative Humidity)	
TEMPRATURE RISE	Less than 70% (Input Volt 180 V, Output Volt 220 V / Phase)	
WORKING SYSTEM	Automatic	
CONTROL SYSTEM	AC Servo Motor + Modul Digital System	
COOLING SYSTEM	Cooling Fan	
DI-ELECTRIC STRENGTH	1500 V/Min	
WAVEFORM DISTORTION	Non-Lack Fidelity Waveform	
INSTALLATION	Indoor	
DIMENSION	PANJANG	130 Cm
	LEBAR	155 Cm x 3 Box + 135 Cm
	TINGGI	233 Cm
BERAT	7.130 Kg	



OVER VOLTAGE PROTECTION



LOW VOLTAGE PROTECTION



OVER TEMP PROTECTION



DELAY TIME

